



**DECLARATION OF PERFORMANCE Nr. 7 (DDP 7)**

**1 – Identification of the Product – Ceramic extruded porcelain floor tiles - Group A1a (E ≤ 0,5 %) – UGL (Un glazed) – Norm EN 14411:2012 (Annex M)**

**2 – Type – All sizes of extruded porcelain floor tiles - Thickness ≥ 7,5 mm**

**3 – Intended use – Floor and Wall coverings for indoors and outdoors**

**4 – Manufacturer Identification:**

Aleluia Cerâmicas S.A.  
 Quinta do Simão – Esgueira  
 3801-101 – Aveiro – Portugal  
 Apartado 3024  
 Telephone : + 351 234 305 600 Fax + 351 234 305 699  
 Email: [geral@aleluia.pt](mailto:geral@aleluia.pt)

**5 – Not applicable**

**6 – System of Assessment / Verification - 4**

**7 – Not applicable**

**8 – Not applicable**

**9 – Declaration of Performance**

<b>PRODUCT: Ceramic Extruded Porcelain Floor Tiles - EN 14411: 2012 - Group A1a (Annex M) – UGL Thickness ≥ 7,5 mm</b>			
<b>Characteristics</b>	<b>Declared Values</b>	<b>Test Method</b>	<b>Norm</b>
Reaction to Fire	Classe A1fl	-----	With no Test Reg. EU nº 305/2011
Mechanical Resistance Flexion Resistance	≥ 1300 N In Conformity	EN ISO 10545 - 4	<b>EN 14411:2012</b>
Mechanical Resistance Modulus of Rupture	≥28 N/mm2 In Conformity		
Durability	Internal Use In Conformity	-----	
	External Use - Frost Resistance	In Conformity	
Thermal Shock Resistance	In Conformity	EN ISO 10545 – 9	
Slipping ( Friction Coefficient)	NPD	-----	
Anti-Slipping (for vehicles circulation)	NPD	-----	
Emission of dangerous substances (Cd and Pb)	NPD	-----	
Gluing Resistance / Adherence	NPD	-----	

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

The present declaration is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Elmano Castilho  
 (Quality and Ambient Director)

Aveiro, 31th January 2014

Código: FR VEN 506 Edição: 1 Revisão: 1 Data: Janeiro 2014